


Rugged Smartphone

E65

5G technology suitable for use
in all environments, even the most difficult



Features

6,5" HD+ display

1D/2D imager

IP67 / 1,5m drops

5 000 mA Hot swappable battery

Android 14 (support up to Android 16)



Specifications

Platform	CPU OS	MTK Dimensity 700 2.2 GHz Octa core Android 14 - up to Android 16
Display	Size Resolution Brightness (cd/m ²)	6,5 inches HD+ 1600 X 720 multi touch, support glove 450 nits
Memory & Storage	ROM RAM Expandable memory	128GB 8GB Micro SD (256Go expansion)
Camera	Rear camera Front camera	13Mpixels with flash and autofocus 5 Mpixels
Wireless	WWAN WLAN GPS WPAN	5G: N1/N3/N7/N8/N20/N28/N41/N77/N78 4G: B1/B3/B7/B8/B20/B28/B34/B38/B40 3G: B1/B8 2G: B3/B8 Wifi 2,4 GHz / 5GHz, IEEE 802.11 a/b/g/n/ac A-GPS, GLONASS, Beidou, GALILEO Bluetooth 5.2 BLE
Sensor & data collection	Barcode Reader RFID/NFC Sensors	1D/2D imager scan engine SE4710 NFC 13,56MHz - ISO 14443A/14443B/15693 G /L /P sensors, Gyro, Hall sensor
Connectors	USB Cradle interface SIM	USB-C (OTG + charging) Charging Dual nano SIM or one nano SIM and one micro SD
Keys	5 keys	on/off + 2 barcode keys + volume keys
Function	Torch PTT Aimer PTI	Yes Yes Yes Ready
Battery	Battery capacity Operating	3,8v 5000mA, li-ion polymere Hot swappable > 10 hours
Dimension	Size Weight	175 x 78,5 x 14,5 mm 285g
Rugged	IP Drop Certificate Temperature	IP67 Multiple time 1,5m MIL-STD-810H Operating : - 20°C to 50°C Storage: -40°C to 70°C
Services	Warranty extension Full Service contract	«continuité» warranty extension total 3 years (return workshops, repair within 10 working days upon receipt of the material - without breakages) «confort» full service contract 3 years (return workshops, repair within 5 working days upon receipt of the material - without breakages)

Accessories

The E65 box include the E65, a battery, a power supply, a USB-C cable , a handstrap and a protective screen already installed



Single Charging cradle
P/N : AT-CAE6502



Handstrap
P/N : AT-CAE6503



Battery
P/N : AT-CAE6501



Bumper
P/N : AT-CAE6505